

MATERIAL SAFETY DATA SHEET

Description: SAF DRAG Revision Number: 02

Document Number: MSDS D009



MEDIUM DUTY WATERBASED DEGREASER

GENERAL

SAF-DRAG is a highly concentrated medium duty water based degreaser that has non corrosive and excellent wetting properties, this product can be used to degrease almost any hard surfaces.

FORMULATION

SAF – DRAG contains exclusive chelating agents for excellent water softening, this product is highly effective even when diluted with water with high hardness. A combination of biodegradable surface active agents is included to ensure economical wetting properties in all types of oil to be removed. Maximum degreasing power is achieved through coupling agents and powerful user friendly solvents.

PRODUCT DESCRIPTION

TEST	UNIT	SPECIFICATION
Appearance		Clear green liquid
Density	g/cm ³	1,03 - 1,05
pH		8.50 – 12.50
Cloud point	°C	5 max

PROPERTIES

- * SAF-DRAG is highly concentrated and can be diluted up to 1:100
- * Non corrosive & non toxic
- * Non flammable & non combustible
- * Anti – redeposit ion properties
- * SAF-DRAG has the unique ability to be mixed either with water or with solvents such as paraffin.

Prepared by: Sabelo Dladla
Reviewed by: Doug Cutter
Status: Issued

Approved by: Doug Cutter
Revision Date: 16 February 2017
Issue Date: 16 February 2017

It is the responsibility of the user to verify that this copy is the latest version.

MATERIAL SAFETY DATA SHEET

Description: SAF DRAG

Revision Number: 02

Document Number: MSDS D009



APPLICATION

Dilutions with water:

SAF- DRAG can be diluted up to 1: 100 as a floor cleaner and 1:25 for cement cleaning & degreasing

When SAF-DRAG is used through a steam-cleaner, the pre-dilution in the tank should be 1:10, whereas the final dilution at the end of the nozzle should be 1:100

For heavy duty degreasing (engine cleaning etc.) dilute SAF-DRAG 1:10 with water.

Light – Medium duty dilute SAF – DRAG from 1:100 – 1:50

Paraffin Mixture:

To combine the solvent properties of Paraffin with the rinsability and detergent cleaning strength of SAF-DRAG in an economical mixture for cleaning engines, parts-washing etc. mix 3 parts of SAF – DRAG with 10 parts Paraffin & 10 parts water.

N.B. This emulsion has to be shaken regularly to avoid separation

THE RECOMMENDATIONS CONTAINED HERE-IN IS BASED ON LABORATORY TESTS AND INFIELD USE EXPERIENCE, AND ARE TO THE BEST OF OUR KNOWLEDGE ACCURATE. SINCE TERMS AND CONDITIONS OF ACTUAL USE ARE BEYOND OUR CONTROL, ALL RECOMMENDATIONS ARE MADE WITHOUT WARRANTY, EXPRESS OR IMPLIED.

Prepared by: Sabelo Dladla
Reviewed by: Doug Cutter
Status: Issued

Approved by: Doug Cutter
Revision Date: 16 February 2017
Issue Date: 16 February 2017

It is the responsibility of the user to verify that this copy is the latest version.

MATERIAL SAFETY DATA SHEET

Description: SAF DRAG Revision Number: 02

Document Number: MSDS D009



Company Details

Name	S.A.F.I.C (PTY) LTD	Tel:	+27 11 406 4000
Address	32 Steele Street, Steeledale	Fax:	+27 11 406 4252
Postal Address	PO BOX 1754, Alberton North, 1450	e-mail:	technical@safic.co.za

1. Product Identification

Trade Name	SAF-DRAG	Product code :	D009
Chemical Family	Water based degreaser (containing surfactants, sequestering & coupling agents.)		
Chemical Name	Formulated chemical		
Product Use	Cleaning and degreasing of most hard surfaces		

2. Composition

CAS No.	Hazardous Components	Approximate %	OSHA PEL
1310-58-3	Potassium hydroxide	<10	CL 2 mg/m ³
111-76-2	Glycol ether	<10	25 ppm TWA, 120mg/m ³
EEC classification	Irritant (Xi), SAF – DRAG		
R Phrases	R36/37/38, SAF – DRAG		

(No free potassium hydroxide available in formulation – reacted with sulphuric acid)

3. Hazards Identification

Main Hazard	Irritant
Fire	Non-flammable
Inhalation	Excess spray – coughing
Skin contact	Irritant. Prolonged or frequent contact may lead to defatting of skin
Eye contact	Irritant. Burning
Ingestion	Symptom: nausea

4. First Aid Measures

Inhalation	Move patient to fresh air.
Skin contact	Rinse area well with water. If necessary, use a hand-cream to replenish moisture.
Eye contact	Flush eyes with water for at least 15 minutes. Irrigate eyes thoroughly while lifting eyelids and rolling eyeballs. If irritation persists, seek medical attention.
Ingestion	Rinse mouth with water, and allow patient as much water as possible. If large quantities have been swallowed obtain medical attention.

5. Fire Fighting Measures

Prepared by: Sabelo Dladla
Reviewed by: Doug Cutter
Status: Issued

Approved by: Doug Cutter
Revision Date: 16 February 2017
Issue Date: 16 February 2017

It is the responsibility of the user to verify that this copy is the latest version.

MATERIAL SAFETY DATA SHEET



Description: SAF DRAG **Revision Number:** 02

Document Number: MSDS D009

Extinguishing media	Product is non-flammable, use extinguishing agents suitable for surrounding fire.
Special hazard	None known
Protective clothing	Approved self contained breathing apparatus should be utilised or equivalent equipment.

6. Accidental Release Measures

Extinguishing media	Product is non-flammable, use extinguishing agents suitable for surrounding fire.
Special hazard	None known
Protective clothing	Approved self contained breathing apparatus should be utilised or equivalent equipment.

7. Handling & Storage

Handling	Normal handling procedure for heavy duty detergents to minimise personal exposure.
Storage	Store in a cool dry area. Keep containers sealed. No special requirements.

8. Exposure Controls/Personal Protection

Workers should have access to an eye wash fountain.
If the specific application may result in splashing, safety goggles (VNC11 supplier – MSA) should be utilised.
Neoprene gloves (Technic 420-supplier MSA) should be utilised.
Work in a well-ventilated area or 6300 type mask/6059 cartridge (3M – supplier) should be utilised where ventilation isn't adequate.

9. Physical and Chemical Properties

Appearance	Clear green liquid
pH	8.50 – 12.50
Density	1.03– 1.05g/cm ³
Cloud point	5 max
Solubility (water)	100 %

10. Stability and Reactivity

Stability	Stable under normal conditions.
Incompatible materials	Strong acids
Hazardous decomposition products	None known

11. Toxicological Information (based on KOH)

Toxicity	Skin (human): 50 mg/24H SEV.
----------	------------------------------

Prepared by: Sabelo Dladla
Reviewed by: Doug Cutter
Status: Issued

Approved by: Doug Cutter
Revision Date: 16 February 2017
Issue Date: 16 February 2017

It is the responsibility of the user to verify that this copy is the latest version.

MATERIAL SAFETY DATA SHEET

Description: SAF DRAG

Revision Number: 02

Document Number: MSDS D009



	Acute oral: LD50 = 365 mg/kg, rat
Carcinogenicity	No evidence of carcinogenic properties
Mutagenicity	No evidence of mutagenetic effects
Teratogenicity	No evidence of teratogenic effects
Reproductive hazard	Not expected to impair fertility

12. Ecological Information (based on glycol ether)

Fathead minnow	96 hr bioassay LC50: 1700 mg/l
Daphnia Magna	48 hr bioassay LC50: >1000 mg/l
Bacterial	IC50: > 5000 mg/l
Biodegradability	Biodegrading: 88 % 20 days
Other Information	The chemical nature of the surfactants needed to remove oil is detrimental to the cell surface membranes of most marine organisms. Most oil dispersants tested by the Sea Fisheries Research Institute show toxicity to sea urchin gametes in the 2 – 20ppm range. SAF-DRAG falls into the normal range for oil dispersants. (1)

Taken from correspondence with the Sea Fisheries Research Institute. Reference V1/1/3/4/5. (1994)

13. Disposal Considerations

Disposal methods identified are for the product as sold. For proper disposal of used material, an assessment must be completed to determine the proper and permissible waste management options permissible under applicable rules, regulations, and/or laws governing your location.

Dilute product 1000 times and run to waste with plenty of water.

When disposing of large quantities, the alkaline nature should be taken into consideration.

14. Transport Information

Substance identity no	D009
ADR/RID class	N/A
IMDG – packaging group	III
Marine Pollutant	No
IMO/IMDG Classification	N/A
IATA Classification	N/A

15. Regulatory Information

EEC-hazard classification	Irritant (Xi)
Risk phrases	R36/37/38
Safety phrases	S24/25 S36

16. Other Information

References: SABS 0265:1999, SABS 0228: 1995, SABS ISO 11014-1:1994, Raw Material Manufacturer's MSDS's

Issued by: Sabelo Dladla

Prepared by: Sabelo Dladla
Reviewed by: Doug Cutter
Status: Issued

Approved by: Doug Cutter
Revision Date: 16 February 2017
Issue Date: 16 February 2017

It is the responsibility of the user to verify that this copy is the latest version.

MATERIAL SAFETY DATA SHEET



Description: SAF DRAG	Revision Number: 02
Document Number: MSDS D009	

EMERGENCY NUMBERS: 011 406 4000 / 082 412 2298

The information in this MSDS is based on current knowledge and experience at the date of publication. This MSDS summarises our best knowledge of the health and safety hazard information of the product and is intended only as a guide to the appropriate precautionary handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification of the product. The data relates only to the specific product designated, and does not relate to use of the product in combination with any other material or use of the product in any process. The data is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability for fitness for a particular purpose is made with respect to the product, its composition, its safety or the information contained in this MSDS sheet.

APPENDIX A

Revision Date (dd/mm/yy)	Issued By	Revision History		Revision No.
		Description	DCN No.	
18/02/2011	Technical Manager	New Issue	MSDS D009	00
20/05/2013	Technical Manager	Document review and change of Company logo.	MSDS D009	01
16/02/2017	Operations Director	Document review, Section 14 revised	MSDS D009	02

Prepared by: Sabelo Dladla Reviewed by: Doug Cutter Status: Issued	Approved by: Doug Cutter Revision Date: 16 February 2017 Issue Date: 16 February 2017
---	--

It is the responsibility of the user to verify that this copy is the latest version.